

UO-1512HW COUNTER-TOP INSTANT WATER BOILER

ACUO
we care about the water you drink



W180 x D360 x H660 (mm)
Depth Excludes Tap

SLIM DESIGN HIGH EFFICIENCY

Provides 40L of hot water above 90°C per hour!

Suitable for restaurants, cafes, hotels, catering services and other venues which requires high volume and capacity of hot water and a space-saving product.

Separator Design

Water faucet positioned at a higher level than the water inlet point which prevents mixing of tap water with boiled water, thus ensures heating efficiency and quality of dispensed water.

Temperature-Controlled Dispense

Suspends water inlet when water in the tank is under 90°C to ensure high temperature.

Heat-Resistant Casing

High density heat-resistant material and Laminated Color Metal for minimal exterior temperature and easy cleaning!

Filter Water Tap

Additional tap for filtered water increases convenience and ease of use on the counter.

Safety Design

Suspends power and water supply when water / electricity leakage or fault is detected.

SPECIFICATIONS

Model	Type	Voltage	Power Consumption	Hot Tank	Hot Water Capacity
UO-1512HW	Hot	220V/60Hz	4KW	18L	40L/HR (above 90°C)

This product is not equipped with any filtration system.

Installation of ACUO's water purifier or filters prior to the boiler is strongly recommended.

*Voltage can be customized based on requirements.
Hot Water 91°C±1°C*

UO-2202HW

UNDER-COUNTER HEAT SERIES WATER BOILER

ACUO
we care about the water you drink



W215 x D280 x H345 (mm)

INSTANT HEATING

Provides instant supply of hot water (90°C or above), no more waiting!

Three-Stage Hot Water Temp. Preservation

Allows setting of hot water at “low”, “medium” or “high” temperature.

Recirculate Sleep Mode Design

Enables energy saving up to 60hrs and automatically reactivates every 24hrs.

Safety Designs

Circuit Leakage Breaker and Zero-Pressure Hot Tank prevent over-heating accidents.

304 Stainless Steel Dual-Temp. Faucet

Insulated faucet with hot water lock and quality hair-brushed finish.



FILTRATION OPTIONS

This product is not equipped with any filtration system.

Installation of ACUO’s water purifier or filters prior to the boiler is strongly recommended.



+ UO-5501JW



+ UO-207



+ UO-5401JW

SPECIFICATIONS

Model	Type	Voltage	Hot Power Consumption	Hot Tank	Hot Water Capacity
UO-2202HW	Hot	110V/220V	750W	4.5L	8L / HR

Voltage can be customized based on requirements.

Hot Water 91°C±1°C